

ChanneLED 5

ChanneLED with SloanStretch



ChanneLED 5 (CL5) offers simplicity and flexibility while providing bright, vivid and uniform illumination. CL5 also features SloanStretch extendable wire function (50 mm) allowing for optimum module placement.

- Run up to 90 modules per 60 W SloanLED DC Power Supply
- Extendable wire feature for optimum module placement
- Constant Current Technology (CCT)
- Peel n' stick or mechanical fastening
- UL, cUL Recognized, CE, CSA Certified



SloanStretch
Extendable wire feature

SPECIFICATIONS:

Dimensions L x W x H	102 mm x 11 mm x 11 mm	
Viewing angle	120°	
LEDs per module	3	
Maximum coverage per row	Can depth	Coverage
	100 mm to 125 mm	150 mm
	≥125 mm	190 mm
Modules per meter	6.5	
Temperature range	-40° C to 70° C	
Protection class	IP66	
Special features	SloanStretch - expandable wire	
Supply voltage	DC 12 V	
Power per module	0.6 W	
Power capacity	90 modules per DC 60 W 12 V power supply	
Fastening	Peel-n-stick and mechanical	
Packaging	50 modules per tray, 5 trays per carton	
Power supply	SloanLED DC 12 V	
Colour	Red	

Item Description	Part Number	Lumens per foot
CL5 Red	701269-R5-MB	35

