

LEDStripe

Large profile LED tubing




For over ten years LEDStripe has added lighting elegance and distinction to buildings worldwide. This patented LED-based rigid tubing system, with its large profile and long runs, has become the border tube system of choice for many retail, restaurant and lodging chains.

- Daytime color when non-illuminated
- High impact acrylic: UV stable, hydrocarbon insensitive, non-fading
- Field cuttable
- Field proven: Over a 305,000 meters of LEDStripe has been installed worldwide

Specifications:

Dimensions



Width	25 mm
Height	43 mm
Lengths	0.6 m, 1.2 m, 1.8 m, 2.4 m

Factory bends

305 mm radius (radial and flat bend)

In-field bends

Radial bend	4.25 m
Flat bend	5.8 m

Temperature range

-40° C to 70° C

Protection class

IP66

Supply voltage

DC 24 V

Power required per meter in

5.0 W on average

Power capacity

DC 24 V 18.3 m

Mounting

Round pre-mounting buttons for standard installation
Slide and mount rectangle mounting buttons for difficult/inaccessible installations

Power supply

SloanLED DC 24 V Power Supply

Colours

Red, orange, amber, lemon yellow, green, blue, white, pastels also available

Accessories


Snap-on, coloured joint covers and corners for clean finish

Approvals

Conforms to UL 48 standard, CE Certified, ETL listed



Item Description	Part # Tube	Approx. Cut Increments	Actual Length
0.6 m Tube	701189-Colour -2	75 mm	635 mm
1.2 m Tube	701189-Colour -4	75 mm	1244 mm
1.8 m Tube	701189-Colour -6	75 mm	1867 mm
2.4 m Tube	701189-Colour -8	75 mm	2477 mm



Mounting Buttons