

Quad 240

240 Watt Power Supply

The Quad 240 is perfect for large LED projects by offering the flexibility to provide power output wattages of up to 240 Watts maximum. The built-in protection circuits for temperature shut down the unit when it reaches unsafe temperatures and will auto restart it when temperatures are again safe to operate. This innovative power supply is robust, flexible, weather resistant, easy to use, and carries UL recognition for dry, damp and wet locations, CSA, TUV and CE certification.



- Use with ChanneLED, ThinLED, ColorLINE and FlexiBRITE
- Simple primary hook-ups, four class 2 outputs
- Proven reliability
- Built-in circuit protection for current, voltage and temperature
- Operating Temperatures -40° to 60° C
- Simple secondary hook-ups – no minimum load, no load balancing and no dip-switches
- UL recognition for dry, damp and wet locations
- Power supplies carry required UL, cUL and CSA, TUV and CE certification
- RoHS and WEEE compliant

Item Description	Part # Number	Nominal Input Voltage	Input Current	Power Output	Enclosure Spec			Overall Dimensions
					Dry	Damp	Wet	
Quad 240 (4 legs)	701495	120-240 Volts	3.0 Amps	240 Watts	X	X	X	9.5"L x 5.9"W x 3.2"H 241mm x 150mm x 81mm

