



Apollo Lighting System

IP68 ChanneLED Module



Apollo LED Lighting System uses one of the most energy efficient LEDs on the market today. It offers industry leading brightness while requiring 50% less power and comes in an attractive soft white color. Apollo has a robust module design (IP68 Ingress Protection), making it the perfect solution for face-lit channel letters and sign cabinets installed in normal and/or extremely damp or wet weather environments.

- Soft white color
- Extremely bright - 50 lm per module*
- 150° Viewing angle
- Completely sealed module (IP68)
- Able to run 56 ft (112 modules) per SloanLED DC 12 V 60 W power supply
- Constant Current Technology

SPECIFICATIONS:

Dimensions L x W x H	3 1/2 in x 3/8 in x 5/8 in	
LEDs per module	3	
Modules per foot	2	
Maximum coverage per row	Can depth	Coverage
	4 in to 5 in	6 in
	>5 in	7 in
Nominal color temperature	5000 K	
Typical brightness	50 lm per module	
Temperature range	-40° C to 65° C	
Protection class	IP68	
Power per module	0.48 W	
Footage per 60W power supply	56 ft (112 modules)	
Fastening	Peel-n-stick and mechanical	
Packaging	25 ft per tray, 5 trays per carton	
Power supply	SloanLED DC 12 V	

Item Description	Part Number	Lumens per foot
Apollo White (5000 K)	701269-W6-MB	100



* Based on preliminary calculated data pending lab testing.