



## SloanLED 12 Volt Power Supply



Modular 60



Self Contained 20

- All SloanLED Power Supplies are rated for Damp Location specification
- Perfect addition to Large Controller (701712-DLO) based system requiring an DC external power supply
- No fuses to replace or circuit breaker to reset. Short Circuit Protection automatically resets when short condition is no longer present
- Simple primary hook-ups and 12 Volt DC Class 2 outputs
- Simple secondary hookups - no minimum load, no load balancing and no dip switches
- Proven reliability, rugged housings
- Limited warranty of up to 5 years

Item Description	LED Power Supplies	
	Self Contained 20	Modular 60
Part Number	701680	701507-MOD
Nominal Input Volts	120/240 Volts	120/240 Volts
Input Current	.3 Amps	1.0 Amps
Output Voltage	12 VDC	12 VDC
Output Current	1.67 Amps	5 Amps
Power Output	20 Watts	60 Watts
Overall Dimensions	3.75"L X 1.6"W X 1"H	9"L X 2.5"W X 2"H

## Jumper Wires



- Can be used anywhere in the LiquaLED system, including between Cluster Lights, Bullet Lights and Perimeter Lights
- Two lengths (2' and 5') are available
- Both versions contain the same Guardian Overmold Connector System found in our other LiquaLED products

